

Flat head plain body steel



> Product Specification

UNIT : mm

F=Flat / K=Knurled / S=Steel / B=Blind

Thread	P/N	T(GRIP RANGE) Min Max	A Rof	Hole Size 0.1	D		B	K	L	(CLOSE END)		
					0.07-0.1					A ₁	L ₁	
M3	FPS-03M-15	0.5-1.5	4.7	5	4.9	7.2	0.8			8.5	10	13.3
	FPS-03M-25	1.5-2.5								9.5		
M4	FPS-04M-20	0.5-2.0	6	6	5.9	8.5	0.8			10.5	11.3	16
	FPS-04M-35	2.0-3.5								12		18
M5	FPS-05M-25	0.5-2.5	7.5	7	6.9	10	1			13	11.5	17
	FPS-05M-50	2.5-5.0								16.5		19
M6	FPS-06M-30	0.5-3.0	9.2	9	8.9	12.3(*13.0)	1.3			15.5	12.7	19.2
	FPS-06M-55	3.0-5.5								19.5		21
M8	FPS-08M-35	1.0-3.5	11.5	11	10.9	14.5(*16.0)	1.5			18.5	14.8	21.5
	FPS-08M-60	3.5-6.0								21		24
M10	FPS-10M-25	0.5-2.5	11.5	13	12.9	16.3	1.5			17		
	FPS-10M-40	2.5-4.0								12.5		13
	FPS-10M-65	4.0-6.0								24		24
	FPS-10M-35(12H)	1.0-3.5	11	12	11.9	16	1.6	19				
M12	FPS-12M-40	1.0-4.0	13.5	13	14.9	18	1.7			22		
	FPS-12M-65	4.0-6.5								25		
	FPS-12M-40(16H)	1.0-4.0								16	16	15.9

All close end pants number add "B", AS:FKS-03M-15B

Manufacturer & Importer

Panel Door Lock / Panel Door Hinges / Latches / Door Handles / Blind Rivet Nut / Mono-Bolt Rivets
 Self Clinching Fasteners / Door gaskets / Fan Filters / Drawer Sliding Chanel